

VCR adapter, male




Illustration only

VCR-adapter, male, stainless steel, DN 40 ISO-KF

- Original Swagelok® VCR Adapter

Dimensions



A 33 mm

Technical Data	VCR-adapter, male, stainless steel, DN 40 ISO-KF
Materials in contact with media	Stainless steel 1.4301 (AISI 304) Stainless steel 1.4401 (AISI 316)
VCR connection	1/4"
Temperature range	196 – 300 °C
Connection flange	DN 40 ISO-KF / G 1/4" VCR
Pressure range	1 · 10 ⁻⁸ hPa – 5 · 10 ² hPa over pressure (elastomer seal); 1 · 10 ⁻⁹ hPa – 5 · 10 ² hPa over pressure (metal seal)
Temperature range max.	300 °C 572 °F 573.15 K
Temperature range min.	196 °C 320.8 °F 77.15 K

Order number	VCR-adapter, male, stainless steel, DN 40 ISO-KF
VCR-adapter, male, stainless steel, DN 40 ISO-KF	120AVM040-0250



Errors and/or changes excepted. - 5/14/2025

Are you looking for an optimum vacuum solution?

Talk to us:

Pfeiffer Vacuum Components & Solutions GmbH Germany

T +49 551 99963-0

info-cs@pfeiffer-vacuum.com

Or scan the barcode, to visit our web page:



<https://webportal.pfeiffer-vacuum.com/global/en/contact>

Follow Us On Social Media

#pfeiffervacuum



www.pfeiffer-vacuum.com

PFEIFFER 