



**Corrugated hose,  
flexible, stainless steel,  
DN 10 ISO-KF, length  
1000 mm**

---



**PFEIFFER** 

# Corrugated hose

PFEIFFER 




Illustration only

**Corrugated hose, flexible, stainless steel, DN 10 ISO-KF, length 1000 mm**

- Flange connection length 15 mm
- Custom lengths on request

## Dimensions



Technical Data	Corrugated hose, flexible, stainless steel, DN 10 ISO-KF, length 1000 mm
Materials in contact with media	Bellows: 316L   Flange: Stainless steel 1.4301/304
Temperature range	196 – 300 °C
Bending radius, frequent movement	100 mm   3.94 inch
Bending radius, one-time movement	17 mm   0.67 inch
Connection flange	DN 10 ISO-KF
Pressure range	$1 \cdot 10^{-8}$ hPa – $5 \cdot 10^2$ hPa over pressure
Material	Flange: stainless steel 1.4301/304; bellows: stainless steel 316L
Temperature range max.	300 °C   572 °F   573.15 K
Temperature range min.	196 °C   320.8 °F   77.15 K

Order number	Corrugated hose, flexible, stainless steel, DN 10 ISO-KF, length 1000 mm
Corrugated hose, flexible, stainless steel, DN 10 ISO-KF, length 1000 mm	120SWN010-1000

Are you looking for an optimum vacuum solution?  
Talk to us:  
**Pfeiffer Vacuum Components & Solutions GmbH Germany**  
**T +49 551 99963-0**  
**info-cs@pfeiffer-vacuum.com**

Or scan the barcode, to visit our web page:



<https://webportal.pfeiffer-vacuum.com/global/en/contact>



Errors and/or changes excepted. - 5/14/2025

Follow Us On Social Media  
#pfeiffervacuum



[www.pfeiffer-vacuum.com](http://www.pfeiffer-vacuum.com)

**PFEIFFER** 