



**Thermocouple
feedthrough, type K, 3
pairs, with MS plug,
DN 16 ISO-KF**



PFEIFFER 

Thermocouple feedthrough, type K




Illustration only

Thermocouple feedthrough, type K, 3 pairs, with MS plug, DN 16 ISO-KF

- 3 Thermocouple pairs type K: Chromel (+) /Alumel (-)
- Thermocouple type E, J on request
- Incl. MS plug as per MIL-C-5015, atmosphere side (-65 to 125 °C)

Dimensions



Technical Data

Thermocouple feedthrough, type K, 3 pairs, with MS plug, DN 16 ISO-KF	
Materials in contact with media	Flange: Stainless steel
Temperature range (vacuum side)	100 – 300 °C
Tightness	1 · 10 ⁻¹¹ Pa m ³ /s 7.5 · 10 ⁻¹¹ Torr l/s 1 · 10 ⁻¹⁰ mbar l/s
Heat up and cool down rate	≤20 K/min
Connection flange	DN 16 ISO-KF
Pressure range	1 · 10 ⁻⁸ hPa – to ambient pressure

Order number	Thermocouple feedthrough, type K, 3 pairs, with MS plug, DN 16 ISO-KF
Thermocouple feedthrough, type K, 3 pairs, with MS plug, DN 16 ISO-KF	120XTK016-3-S

Are you looking for an optimum vacuum solution?
Talk to us:
Pfeiffer Vacuum Components & Solutions GmbH Germany
T +49 551 99963-0
info-cs@pfeiffer-vacuum.com

Or scan the barcode, to visit our web page:



<https://webportal.pfeiffer-vacuum.com/global/en/contact>



Errors and/or changes excepted. - 5/14/2025

Follow Us On Social Media
#pfeiffervacuum



www.pfeiffer-vacuum.com

PFEIFFER 