




A red pole with many white directional signs pointing in various directions, each displaying a distance in kilometers. The signs are arranged in a circular pattern around the pole, with distances ranging from 560 km to 9,658 km. The background is a clear blue sky.

PFEIFFER 

Reducing piece, conical


PFEIFFER 



Illustration only

Conical reducing piece, stainless steel 304/1.4301, DN 160/100 ISO-K

Dimensions



Technical Data	Conical reducing piece, stainless steel 304/1.4301, DN 160/100 ISO-K
Materials in contact with media	Stainless steel 1.4301 (AISI 304)
Nominal diameter reduced	DN 100 ISO-K
Temperature range	196 – 300 °C
Connection flange	DN 160 ISO-K / DN 100 ISO-K
Pressure range	1 · 10 ⁻⁸ hPa – 5 · 10 ² hPa over pressure (elastomer seal); 1 · 10 ⁻⁹ hPa – 5 · 10 ² hPa over pressure (metal seal)
Temperature range max.	300 °C 572 °F 573.15 K
Temperature range min.	196 °C 320.8 °F 77.15 K

Order number	Conical reducing piece, stainless steel 304/1.4301, DN 160/100 ISO-K
Conical reducing piece, stainless steel 304/1.4301, DN 160/100 ISO-K	320RRK160-100-104

Are you looking for an optimum vacuum solution?
Talk to us:
Pfeiffer Vacuum Components & Solutions GmbH Germany
T +49 551 99963-0
info-cs@pfeiffer-vacuum.com

Or scan the barcode, to visit our web page:



<https://webportal.pfeiffer-vacuum.com/global/en/contact>



Errors and/or changes excepted. - 5/14/2025

Follow Us On Social Media
#pfeiffervacuum



www.pfeiffer-vacuum.com

PFEIFFER 