

Thermocouple feedthrough, type K, 2 pairs, DN 40 CF



PFEIFFER 

Thermocouple feedthrough, type K

PFEIFFER ➤





Illustration only

Thermocouple feedthrough, type K, 2 pairs, DN 40 CF

- 2 Thermocouple pairs type K: Chromel (+) /Alumel (-)
- Thermocouple types C, E, J, T, N, R, S on request
- Vacuum-side lugs with screw connections for the thermo wire (including screws)
- Including atmosphere sided miniature plug (-65 to 125 °C)

Dimensions



Technical Data	Thermocouple feedthrough, type K, 2 pairs, DN 40 CF
Materials in contact with media	Flange: Stainless steel
Temperature range (vacuum side)	100 – 300 °C
Tightness	$1 \cdot 10^{-11}$ Pa m ³ /s $7.5 \cdot 10^{-11}$ Torr l/s $1 \cdot 10^{-10}$ mbar l/s
Heat up and cool down rate	≤20 K/min
Connection flange	DN 40 CF
Pressure range	$1 \cdot 10^{-11}$ hPa – to ambient pressure

Order number	Thermocouple feedthrough, type K, 2 pairs, DN 40 CF
Thermocouple feedthrough, type K, 2 pairs, DN 40 CF	420XTK040-2

Are you looking for an optimum vacuum solution?
Talk to us:
Pfeiffer Vacuum Components & Solutions GmbH Germany
T +49 551 99963-0
info-cs@pfeiffer-vacuum.com

Or scan the barcode, to visit our web page:



<https://webportal.pfeiffer-vacuum.com/global/en/contact>



Errors and/or changes excepted. - 5/14/2025

Follow Us On Social Media
#pfeiffervacuum



www.pfeiffer-vacuum.com

PFEIFFER 