

**Quick-Access door, with
sight glass, stainless
steel 304/1.4301,
DN 100 ISO-F**



PFEIFFER 


Quick-Access door, with sight glass



Illustration only

Quick-Access door, with sight glass, stainless steel 304/1.4301, DN 100 ISO-F

Dimensions



Technical Data	Quick-Access door, with sight glass, stainless steel 304/1.4301, DN 100 ISO-F
Materials in contact with media	Stainless steel 1.4301 (AISI 304)
Number of screws	8 Pieces
Seal	FKM
O-ring material	FKM
Temperature range	15 – 150 °C
Sight glass	Borosilicate glass
Connection flange	DN 100 ISO-F
Pressure range	1 · 10 ⁻⁸ hPa – to ambient pressure
Temperature range max.	150 °C 302 °F 423.15 K
Temperature range min.	15 °C 5 °F 258.15 K

Order number	Quick-Access door, with sight glass, stainless steel 304/1.4301, DN 100 ISO-F
Quick-Access door, with sight glass, stainless steel 304/1.4301, DN 100 ISO-F	520KTU100-G

Are you looking for an optimum vacuum solution?
Talk to us:
Pfeiffer Vacuum Components & Solutions GmbH Germany
T +49 551 99963-0
info-cs@pfeiffer-vacuum.com

Or scan the barcode, to visit our web page:



<https://webportal.pfeiffer-vacuum.com/global/en/contact>



Errors and/or changes excepted. - 5/14/2025

Follow Us On Social Media
#pfeiffervacuum



www.pfeiffer-vacuum.com

PFEIFFER 